# Data sheet



## PURION POOL 40 Compact system

#### **DESCRIPTION**

With the PURION 40, pools up to 30m³ can be cleaned. The coordinated system consists of a robust pump, a sand filter with grain-free granulate and an ecological UV-C system. The UV-C system means that chlorine no longer has to be used for the pool. This system was designed by experts with many years of pool experience in such a way that no time-consuming installation or calculation is required.

#### **OPTIONAL MONITORING LEVELS**

**Basic (without monitoring option)** 

### Plus (OTC/lifetime monitoring)

The UV-C lamp has a natural drop in performance over the duration of its service life (10,000h). After this time, the lamp must be changed, the lamp runtime meter and the lifetime monitoring (OTC) signal the right time. The hours in which the lamp is switched on are counted and the values are output via an LED display. Up to 9,000 hours a green LED lights up, between 9,000 and 10,000 hours the pre-alarm is indicated by a yellow LED and after 10,000 hours a red LED lights up.

### **Scope of delivery**

- UV compact system
- 25 kg coarse quartz glass granulate
- 25 Kg fine quartz glass granulate
- UV lamp (48 W)
- Operating instructions



# **Technical data**

Manufacturer	PURION GmbH	Filter tank material	Polyethylene
Туре	PURION POOL 40	Power consumption pump	0.55 kW
Pool size	30m³ (15h operation), 20m³ (10h operation)	Quantity of special quartz	35 kg
Dimensions L x W x H in mm	770 x 530 x 940	Filter medium (granulate)	AFM active
Weight (without filling filter tank)	34 kg	Valve Filter tank	4-way valve on top
UVC system	PURION 2001 (48 W)	Connection	<ul><li>Adapter for:</li><li>Adhesive sleeve D50</li><li>Hose nozzle D40/32</li></ul>
Lamp operating time	10.000h	Electrical connection	230V 50hz
Temperature range	2 - 40°C	Fuse protection	10A
Flow rate	6m³/h	Enclosure protection	IP 54



