Data sheet

UV Concept GmbH

PURION POOL 80 Compact system

DESCRIPTION

With the PURION 80, pools up to 90m³ can be cleaned. The coordinated system consists of a robust pump, a sand filter with grain-free granulate and an ecological UV-C system. It is characterized by an extraordinarily high disinfection performance with a compact design and low energy consumption.

OPTIONAL MONITORING LEVELS

Basic (without monitoring option)

Plus (OTC/lifetime monitoring)

The UV-C lamp has a natural power decrease over the duration of its lifetime (10,000h). After this time the lamp must be changed, the lamp runtime meter and the lifetime monitoring (OTC) signal the right time. The hours in which the lamp is switched on are counted and the values are output via an LED display. Up to 9,000 hours a green LED lights up, between 9,000 and 10,000 hours the pre-alarm is indicated by a yellow LED and after 10,000 hours a red LED lights up.

Scope of delivery

- UV compact system
- 50 kg coarse quartz glass granulate
- 50 Kg fine quartz glass granulate
- UV lamp (90 W)
- Instruction manual



Technical data

| Manufacturer | PURION GmbH | Filter tank material | Polyethylen |
|--|--|--|---|
| Туре | PURION POOL 80 | Power consumption pump | 0.75 kW |
| Pool size | 80 m³ (20h operation) 60 m³ (15h operation) | Quantity of special quartz | 85 kg |
| Dimensions L x W x H in mm | 850 x 630 x 1290 | Filter medium (granules) | AFM active |
| Weight (without filling filter tank) | 48 kg | Valve Filter tank | top mount 4 Wegeventil |
| UVC system | PURION 2501 (90 W) | Connection | Adapter for: • Adhesive sleeve D50 • Hose nozzle D40/32 |
| Radiation usage time | 10.000h | Electrical connection | 230V AC |
| Temperature range | 2 - 40°C | Fuse protection | 10A |
| Flow rate | 12 m³/h | Housing protection | IP 54 |
| info@uvconcept.com T Tel: +49 3641 327 9697 C | JV Concept GmbH Thomas-Mann-Straße 27 07743 Jena www.uvconcept.com | Official PURION Distributor PURION® DIE SICHERSTE LÖSUNG | UVC-Desinfection Made in Germa |